

# FC 460



## DATI TECNICI

Pompa a vuoto:	bagno d'olio - 25 mc/h
Dimensioni:	mm 600x700x500h
Dimensioni camera:	mm 485x550x175h
Tensione:	220/240 V - 50/60 Hz
Peso:	kg 96

## DONNEES TECHNIQUES

Pompe a vide:	à bain d'huile - 25 mc/h
Dimensions:	mm 600x700x500h
Dimensions chambre:	mm 485x550x175h
Voltage:	220/240 V - 50/60 Hz
Poids:	kg 96

## TECHNICAL DATA

Vacuum pump:	oil-lubricated - 25 mc/h
Size:	mm 600x700x500h
Chamber size	mm 485x550x175h
Power grid voltage:	220/240 V - 50/60 Hz
Weight:	kg 96

## DATOS TECNICOS

Bomba vacío:	aceite - 25 mc/h
Medidas:	mm 600x700x500h
Medidas de la cámara:	mm 485x550x175h
Tensión:	220/240 V - 50/60 Hz
Peso:	kg 96

## BARRA SALDANTE - SEALING BEAM

1x455 mm - 2x455 mm - 2x520 mm

## OPTIONALS - OPTIONALS - OPTIONS - OPCIONES

### DESCRIZIONE

Gas - Gas - Gaz - Entrada de gas inerte

Sensore di vuoto - Sensor - Capteur de vide - Sensor

Softair - Softair - Softair - Softair

Taglio sfrido - Cut of seal - Coupe sachets - Recorte sobrante de bolsa

Barra opzionale - Double beam - Double barre de soudure - Barra de soldadura extra